
Stainless Steel Banding

Product Description/ Specification:

Austenitic Stainless Steel ASTM A240/ ASTM A167/ EN 10088-4.

Metal Banding are used as fixing system in insulation, construction and sign industry. BS Stainless specialise in the supply of high performance banding for all applications. Banding are manufactured in the UK within the scope of ISO 9001:2008 management system.

We mainly supply 316/316L grade, other grades and materials including Aluminium alloy or galvanised steel are also available to order.

We also supply painted banding for identification and aesthetic applications. For high corrosion resistance, we can supply banding with factory applied moisture barrier. For more details, please refer to painted banding datasheet and DryMet band datasheet.

Dimensions:

Standard Widths of Banding Supplied are:

1/2" (13mm), 3/4" (19mm), 1" (25mm) and 1.2" (30mm), different widths can also be produces on request. Most Common thickness—0.4mm & 0.5mm, different thicknesses can be produced as per requirement

Tolerance:

Thickness +/- 0.1 mm and Width +/- 1 mm

Packaging:

All coils are in 100 foot rolls.

Materials will be shipped on wooden pallets approximately 1000mm X 1200mm X 500mm and shrink wrapped. Heat treated pallets will be supplied where requested.

Finish:

The finish will not affect the properties or application of the materials, it is completely visual. The material finish for banding is BA (bright finish).

